

Professional Mobile Refrigeration

T0022/NDN
T0022/FDN
T0022/FDH



T0032/NDN
T0032/FDN
T0032/FDH



T0056/NDN
T0056/FDN
T0056/FDH



T0082/NDN
T0082/FDN
T0082/FDH



F0140/NDN
F0140/FDN
F0140/FDH



F0330/NDN
F0330/FDN
F0330/FDH



F0720/NDN
F0720/FDN
F0720/FDH



F0915/NDN
F0915/FDN
F0915/FDH



Type	Top Loader		Top Loader		Top Loader		Top Loader		Front Loader		Front Loader		Front Loader		Front & Side Loader	
Volume in litres	22		32		56		82		140		330		720		915	
External dimensions	590 x 380 x 480		670 x 390 x 480		800 x 500 x 500		940 x 560 x 550		1000 x 620 x 710		1020 x 1000 x 910		1100 x 1400 x 1100		1500 x 1200 x 1180	
Internal dimensions	290 x 230 x 350		360 x 250 x 350		450 x 330 x 350		540 x 370 x 360		620 x 410 x 510		810 x 610 x 660		850 x 1020 x 780		290 x 230 x 350	
Wall thickness	65 - 70		65 - 70		70		80		80 - 100		100		120		130	
Thermostat	Digital		Digital		Digital		Digital		Digital		Digital		Digital		Digital	
Voltage DC	12-24v DC		12-24v DC		12-24v DC		12-24v DC		12-24v DC		12-24v DC		12-24v DC		12-24v DC	
Voltage AC	100-240v AC		100-240v AC		100-240v AC		100-240v AC		100-240v AC		100-240v AC		100-240v AC		100-240v AC	
Weight	17		19		26		29		40 45		90 95		165 170		160 170	
Temperature	> -24°C		> -24°C		> -24°C		> -24°C		> -10°C > -21°C		> +0°C > -21°C		> +1°C > -21°C		> +1°C > -21°C	
Maximum consumption	9A (12v)		9A (12v)		9A (12v)		9A (12v)		9A (12v) 18A (12v)		9A (12v) 18A (12v)		18A (12v) 25A (12v)		18A (12v) 25A (12v)	
Compressor type	1 x BD50F		1 x BD50F		1 x BD50F		1 x BD50F		1 x BD50F 1 x BD80F		1 x BD50F 1 x BD80F		1 x BD80F 1 x BD220F		1 x BD80F 1 x BD220F	
Options available	<+40°C>24°C		<+40°C>24°C		<+40°C>24°C		<+40°C>24°C		<+40°C > -10°C		<+30°C > +0°C		TBC TBC		TBC TBC	



In addition to the base range we are able to provide solutions to compliment every operation including;

- Battery power support
- Solar power charging
- Temperature recording and data logging
- Integration with temperature tracking systems